

20/04/2007

**FAMILY** PREPARACIONES, FONDOS E IMPR.**LINE** AL USO (MASILLAS)**DESCRIPTION AND NATURE**

Extremely elastic waterproof putty. Specially formulated to treat cracks and fissures. Incorporates fibre materials which intensify its action.

**USAGES**

Outdoors/Indoors  
 NO TRADUCIDO, NO TRADUCIDO  
 NO TRADUCIDO

**PROPERTIES**

Applicability  
 Do not crack  
 Elasticity  
 Waterproof  
 Odourless  
 Does not decrease  
 Complement for Tejamont

**TECHNICAL CHARACTERISTICS**

Finish	Matt
Specific weight	1,38 +- 0,05 kg/l
Solids in volume	53,80%
Solids in weight	68,50%
Minimum recommended thickness	1 mm
Aproximated performance by cover	Depending of product usage
Touch dryness	(20°C HR: 60%, 1mm): 4-8 h
Re-painting	24-48h
Colours	White

**SURFACE PREPARING****New surfaces**

Plaster and mortar cement:

- Bad condition surfaces should be anchored with Fijamont, Emulsión Fijadora or Fijalite.
- Test PLASMONT FIBRA ELASTICO suitability on surface.
- Wait till complete drying of product (30 days).
- Remove off any efflorescences and neutralize alkaline surfaces.
- Extremely polished surfaces should be sandpapered to open pores.
- Remove off any foreign products or remains.
- Open any fissures or cracks until obtaining good condition surface. Remove off any resulting dust by brushing and apply product as recommended under Application Systems and Application points.

**Restoring and maintenance**

Remove off any remains or peeling of product or any other foreign product. Open pore by sandpapering or any other mechanical systems.  
 Check adherence level and treat as per new surfaces.

20/04/2007

## WAY OF USE

### Application Notes

-Use only recommended clean and dust-free tools as per Application Systems.

-Only repaint after indicated drying time, which depends on moisture and temperature conditions as well as coat thickness.

### Solvent for dilution and cleaning

Water

### Way of use

Large Pallette

Pallette

### Aproximate dilution

al uso

al uso

## SYSTEM

### Procedures depending of surface type

	Primer	Intermedium	Finish
<b>New wood/old outdoor</b>			
MAX			
STD	Montopol fondo	Plasmont Elástico	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont
<b>Old/New interior Wood</b>			
MAX			
STD	Plasmont Elastico	Fijador (Emulsión Fijadora)	Montoplástica, Ovaldine, Montonature, Montokril, Tejamont

## NOTE

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to stablish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

## PACKINGS

0.15 L, 0.3 L, 0.75 L, 2.5 L