



VAGANS 25

Product description:

Vagans 25 is a water based semi-matt, washable and humidity rejecting acrylic paint with high cover. This product is suitable for painting walls and ceilings indoors in vulnerable areas which demands high washability and/or is exposed for humidity. The paint gives a durable, smudge-resistant surface and contains all necessary components for painting in wet locations.

Vagans 25 is ideal for kitchen, hall and in public environment. Suitable foundation is concrete, plaster, fabrics, wall paper and earlier painted surfaces. Vagans 25 is produced in Sweden and it's included in Colorex Mix tinting system.

TECHNICAL DATA:

Area of application	Indoors
Binder	Styrene acrylic
Volume Solids	34%
Density	1,23 kg/l
Gloss	25 (semi matt)
Washability	Class 1 (EN 13300)
Thinner/Cleaning	Water
Material consumption	5–8 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, roller and spray
Dust dry	1 h
Re-paintable	2-4 h
Completely dry	24 h
Colour	White
Flammability	Not Flammable
VOC category	(Cat A/a): 30 g/l (2010)



VAGANS 25

How to use:

Pre-painting

Always start by reading the instructions on the label. It's important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir the paint properly from the bottom before starting to paint. Make sure that the surface is clean, dry and free from dust. Putty all holes and unevenness's. Sand carefully when the putty is dry and dust the surface with a lightly moistened cloth. Wash earlier painted surfaces with appropriate cleaner and rinse with water. Glossy – previous alkyd painted surfaces– must be sanded matt before painting. When painting glass fibre fabrics in wet rooms, special glue and putty, intended for wet rooms, must be used. Protect floor and furniture properly before starting to paint.

Painting

Start by painting the ceiling walls around doors and windows with a brush. Paint 1–2 times for an even result with full cover. When painting glass fibre fabrics in wet rooms, paint at least three times. If your walls are smooth we recommend a roller with short nap. If they are rougher, a roller with longer nap is more suitable. Vagans 25 becomes dry in 30 minutes and it is able to repaint after 2–4 hours. In approximately 48 hours it's completely dry.

Post-painting

Wipe off the tools thoroughly before cleaning in water and a mild cleaning liquid. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

Maintenance

Be careful when cleaning surfaces painted with acrylic paint with lower gloss, since the paint has a more sensitive finish. Use a damp rag and possibly some mild cleaning liquid to clean the surface. Never use spirits when cleaning painted or lacquered surfaces. Resistant against normal household chemicals.