



**COPRABEL**  
*Quality in Colors*

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7  
BE-1300 Wavre Belgium  
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89  
www.coprabel.com info@coprabel.com



# TECHNICAL DATA SHEET

## EASY COLOR® SILVER 905

---

### DESCRIPTION

---

EASY COLOR® SILVER 905 is a 100% acrylic resin, metallic solvent-based paint that offers high brilliance and good resistance for all interior/exterior projects.

This ready-to-use, DIY and easy-to-use paint can be applied on wood derivatives, plaster, metallic surfaces and non-ferrous metals which are properly prepared.

Whether it is applied on small decorative pieces or on large-scale works, EASY COLOR® SILVER 905 metallic paint is suitable for all design needs: it can give a warm vintage look in your living room, an industrial finish to your offices or a glamorous touch to your hotel lobby!

This shade is suitable for indoor and outdoor when it is covered by the appropriate top coat. For optimal resistance, combine it with our EASY COLOR® ACRYLIC VARNISH for indoors and our NARI® 2K PU for outdoors.

---

### PRECAUTIONS

---

- Mix carefully before use.
- Avoid contact with eyes and skin.
- Wear protective clothes, glasses and gloves.
- Keep out of reach of children.
- Keep products away from frost and from heat sources.
- Do not dispose of residual paint by flushing it away.
- Take appropriate precaution when disposing of the packages.
- Consult the Safety Data Sheet for more details.



**COPRABEL**  
*Quality in Colors*

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7  
BE-1300 Wavre Belgium  
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89  
www.coprabel.com info@coprabel.com



## TECHNICAL DATA SHEET

### EASY COLOR® SILVER 905

#### METHOD OF USE

Surface preparation	According to the substrates: remove pre-existing paint, degrease with water and soap or washing diluent, sand and dust. New substrate: prepare the surface with the appropriate primer.
Application & Dilution	Stir thoroughly before and while using. Brush and roll: ready to use. Spray: dilute with 5 to 10% thinner. Wear safety gloves and spray mask.
Drying time	2 hours at 23°C and 50% relative humidity.
Recoatable	After 24 hours.
Cleaning of Material	With Thinner.
Shelf life	5 years in original and sealed can.

#### TECHNICAL SPECIFICATIONS

Aspect	Metallic, high silver brilliance.
Composition	Binder: 100% acrylic resins in solutions. Pigment: aluminium powder. Solvents: Aromatic hydrocarbons.
Thickness Dry Film	10 µ on an average.
Solid Content	Weight %: 24.88.
Density	0.97 g/cm <sup>3</sup> ± 0.05 at 20°C.
Flash Point	23°C.
Coverage	± 15 - 20m <sup>2</sup> /L per coat.
Packaging	125 ML - 250 ML - 500 ML - 750 ML.



**COPRABEL**  
*Quality in Colors*

COPRABEL S.A Z.I. Wavre-Nord, Avenue Lavoisier, 7  
BE-1300 Wavre Belgium  
Tel: +32 10 23 82 80 Fax: +32 10 23 82 89  
www.coprabel.com info@coprabel.com



# TECHNICAL DATA SHEET

## EASY COLOR® SILVER 905

### REMARKS AND RECOMMENDATIONS

Store in a well-ventilated and dry room at temperatures between 10°C and 30°C. Higher temperature could have a significant influence on drying time. Relative humidity of the environment: <80%. Protect from heat and direct sunlight. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

For a long-lasting effect and protection, use EASY COLOR® ACRYLIC VARNISH (solvent or water-based) as a final coat for indoor use. For outdoor projects, to avoid oxidation and peeling, use our NARI® 2K PU as topcoat.

Warranty invalid if other system than provided by COPRABEL S.A. is used.

*Note: Cancels and replaces the former editions. It's up to our customers to check, before application, if it is indeed the latest edition. The information contained in this note has only one indicative range and cannot compensate a description suitable with the nature and the state of surface to be treated.*