

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 421-E10S905
Trade name/designation EASY COLOR SILVER PAINT 905

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:
paint and varnish

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

COPRABEL SA
avenue Lavoisier 7 Telephone: +32 (0)10 238 280
B-1300 WAVRE Telefax: +32 (0)10 238 289

Information contact:

Laboratory
E-mail info@coprabel.com
Website http://www.coprabel.com

1.4. Emergency telephone number

Emergency telephone number +32 (0)10 238 280
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapour.
P271 Use only outdoors or in a well-ventilated area.
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 2 / 10

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Keep locked up.
P501 Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

Xylene
Hydrocarbures, C9, aromatiques

Supplemental hazard information

not applicable

2.3. Other hazards

No information available.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Description Colour

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	Wt %
CAS No.	Designation	
INDEX No.	classification // Remark	
215-535-7	01-2119488216-32	
1330-20-7	Xylene	25 - 50
601-022-00-9	Flam. Liq. 3 H226 / Acute Tox. 4 H312 / Acute Tox. 4 H332 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Asp. Tox. 1 H304 / STOT RE 2 H373 / STOT SE 3 H335	
918-668-5	01-2119455851-35	
64742-95-6	Hydrocarbures, C9, aromatiques STOT SE 3 H335 / STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 3 H226	25 - 50
231-072-3	01-2119529243-45	
7429-90-5	POUDRE ALUMINIUM STABILISEE Flam. Sol. 1 H228 Substance with a common (EC) occupational exposure limit value.	12,5 - 20
918-481-9	01-2119457273-39	
64742-48-9	Hydrocarbons, C10-C13, n alcanes, isoalcanes, cycliques < 2% aromatiques Asp. Tox. 1 H304	2,5 - 5
202-849-4	01-2119489370-35	
100-41-4	ethylbenzene	2,5 - 5
601-023-00-4	Flam. Liq. 2 H225 / Acute Tox. 4 H332 / STOT RE 2 H373 / Asp. Tox. 1 H304	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 3 / 10

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 4 / 10

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

WEL, TWA: 220 mg/m³; 50 ppm

WEL, STEL: 441 mg/m³; 100 ppm

Remark: (may be absorbed through the skin)

BMGV, TWA: 650 mmol/mol creatinine

Remark: methyl hippuric acid; urine; end of exposure or end of shift

ethylbenzene

INDEX No. 601-023-00-4 / EC No. 202-849-4 / CAS No. 100-41-4

WEL, TWA: 441 mg/m³; 100 ppm

WEL, STEL: 552 mg/m³; 125 ppm

Remark: (may be absorbed through the skin)

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

DNEL long-term dermal (systemic), Workers: 180 mg/kg

DNEL acute inhalative (local), Workers: 289 mg/m³

DNEL acute inhalative (systemic), Workers: 289 mg/m³

DNEL long-term inhalative (systemic), Workers: 77 mg/m³

DNEL long-term dermal (systemic), Consumer: 108 mg/kg

DNEL acute inhalative (local), Consumer: 174 mg/m³

DNEL acute inhalative (systemic), Consumer: 174 mg/m³

DNEL long-term inhalative (systemic), Consumer: 14,8 mg/m³

Hydrocarbures, C9, aromatiques

EC No. 918-668-5 / CAS No. 64742-95-6

DNEL long-term dermal (systemic), Workers: 25 mg/kg

DNEL long-term inhalative (systemic), Workers: 150 mg/m³

DNEL long-term oral (repeated), Consumer: 11 mg/kg

DNEL long-term dermal (systemic), Consumer: 11 mg/kg

DNEL long-term inhalative (systemic), Consumer: 32 mg/m³

PNEC:

Xylene

INDEX No. 601-022-00-9 / EC No. 215-535-7 / CAS No. 1330-20-7

PNEC aquatic, freshwater: 0,327 mg/l

PNEC aquatic, marine water: 0,327 mg/l

PNEC sediment, freshwater: 12,46 mg/kg

PNEC sediment, marine water: 12,46 mg/kg

PNEC, soil: 2,31 mg/kg

PNEC sewage treatment plant (STP): 6,58 mg/l

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 5 / 10

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: refer to label

Odour: characteristic

Odour threshold: not applicable

pH at 20 °C: not applicable

Melting point/freezing point: not applicable

Initial boiling point and boiling range: 137 °C
Source: Xylene

Flash point: 23 °C
Method: DIN 53213

Evaporation rate: not applicable

flammability

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 1 Vol-%
Upper explosion limit: 7,8 Vol-%
Source: ethylbenzene

Vapour pressure at 20 °C: 4,0817 mbar

Vapour density: not applicable

Relative density:

Density at 20 °C: 0,97 g/cm³

Solubility(ies):

Water solubility (g/L) at 20 °C: insoluble

Partition coefficient: n-octanol/water: see section 12

Auto-ignition temperature: 255 °C

Source: Hydrocarbons, C10-C13, n alkanes, isoalcanes, cycliques < 2% aromatiques

Decomposition temperature: not applicable

Viscosity at 20 °C: 14 s 4 mm

Method: DIN 53211

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 6 / 10

Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
Solid content (%):	25 Wt %
solvent content:	
Organic solvents:	75 Wt %
Water:	0 Wt %

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

ethylbenzene

oral, LD50, Rat: > 3500 mg/kg

dermal, LD50, Rabbit: > 15000 mg/kg

inhalative (vapours), LC50, Rat: > 20 mg/l (4 h)

Hydrocarbons, C10-C13, n alkanes, isoalkanes, cycliques < 2% aromatiques

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rat: > 2000 mg/kg

Xylene

oral, LD50, Rat: 4300 mg/kg

dermal, LD50, Rabbit: 1700 mg/kg

inhalative (vapours), LC50, Rat: 21,7 mg/l (4 h)

Hydrocarbures, C9, aromatiques

oral, LD50, Rat: > 3492 mg/kg

inhalative (Gases), LC50, Rat (4 h)

inhalative (vapours), LC50, Rat: 10,2 mg/l (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Xylene

Skin (4 h)

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 7 / 10

May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Xylene

Specific target organ toxicity (single exposure)
Specific target organ toxicity (single exposure), Irritation

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
Do not allow to enter into surface water or drains.

12.1. Toxicity

ethylbenzene

Fish toxicity, LC50: > 10 mg/l (96 h)
Daphnia toxicity, EC50: > 1,8 mg/l (48 h)
Algae toxicity, ErC50: 3,6 mg/l (96 h)

Xylene

Fish toxicity, LC50 1 - 10 mg/l (96 h)
Daphnia toxicity, EC50 1 - 10 mg/l (48 h)
Algae toxicity, ErC50 1 - 10 mg/l

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Xylene

Fish toxicity, LC50 (96 h)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 8 / 10

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

- 14.1. **UN number**
UN 1263
- 14.2. **UN proper shipping name**
Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint
- 14.3. **Transport hazard class(es)**
3
- 14.4. **Packing group**
III
- 14.5. **Environmental hazards**
Land transport (ADR/RID) UMWELTGEFÄHRDEND
Marine pollutant p / Hydrocarbures, C9, substances
- 14.6. **Special precautions for user**
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8
- Further information**
- Land transport (ADR/RID)**
tunnel restriction code D/E
- Sea transport (IMDG)**
EmS-No. F-E, S-E
- 14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information

- 15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**
- Directive 2010/75/EU on industrial emissions**
VOC-value (in g/L): 723
- Directive 2004/42/EC on the limitation of emissions of volatile organic compounds**
VOC product category: (Cat. A/h) ; VOC limit value: 750 g/l
Maximum VOC content (g/L) of the product in a ready to use condition: 723
- National regulations**
- Restrictions of occupation**
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
- 15.2. **Chemical Safety Assessment**
For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
215-535-7 1330-20-7	Xylene	01-2119488216-32
918-668-5 64742-95-6	Hydrocarbures, C9, aromatiques	01-2119455851-35
918-481-9 64742-48-9	Hydrocarbons, C10-C13, n alcanes, isoalcanes, cycliques < 2% aromatiques	01-2119457273-39

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
 Print date: 30.04.2020 Revision date: 07.11.2019
 Version: 30-2 Issue date: 07.11.2019

EN
 Page 9 / 10

202-849-4 ethylbenzene
 100-41-4

01-2119489370-35

SECTION 16: Other information

Full text of classification in section 3

Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Flam. Sol. 1 / H228	flammable solids	Flammable solid.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
STOT RE 2	STOT-repeated exposure	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 421-E10S905 EASY COLOR SILVER PAINT 905
Print date: 30.04.2020 Revision date: 07.11.2019
Version: 30-2 Issue date: 07.11.2019

EN
Page 10 / 10

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.