

Fecha de Alta

11-05-2021

Versión

2 - 07/01/2022 12:1



FAMILY PAREDES Y TECHOS

LINE MATE

DESCRIPTION AND NATURE

Acrylic plastic paint, for decoration and protection of walls and ceilings. Ideal for generating an appearance of absolute cleanliness and freshness.

USAGES

Indoors

Cement

Cement

Concrete

Brick

Gypsum Board

Plaster

PROPERTIES

- Whiteness
- Low odour
- High sweating
- Good covering in dry
- Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	REHABIT P5 ULTRABLANC
Finish	Matt
Specific weight	1,61± 0,05 kg/l
Viscosity	110 +/- 25 PO
Solids in volume	42± 1
Solids in weight	65± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,69 g/l
Aproximated performance by coat	7-9 m ² /L

Dry to touch	(20°C HR:60%): 1 h
Dry to repaint	(20°C HR:60%): mín 3-4 h
Colours	White Tint with universal dye or with water, máx 5%
Classification	AFNOR: NFT. 36005 Famille I Classe 7b2

SURFACE PREPAIRING

New surfaces

Cement mortars:

1. Hope until forged total (mín 30 days).
2. Clean the possible efluorescencias with abrasive spurt.
3. Neutralize the alkaline surfaces.
4. Polished surfaces: to sandpaper .
5. Clean the strange product on support.
6. Fix the weak supports with fixer.
7. Fill in defects in the substrate.

Plaster:

1. Wait till complete drying of product (20% max. Moisture level).
2. Clean the strange product on support.

Fecha de Alta

11-05-2021

Versión

2 - 07/01/2022 12:1

3. Clean the possible eflorescencias with abrasive spurt.
4. Regulate the absorptions of the support with selladora, Locking device, or a diluted hand of he himself product
5. Polished surfaces: to sandpaper to open pore
6. Fix the weak supports with fixer.
7. Fill in defects in the substrate.

Restoring and maintenance

- 1 - Eliminate old paintings in badly been or badly adhered totally.
- 2 - Shining surfaces must be clarified, to make sure a good adhesion.
- 3 - On painted supports it must verify the solidity and anchorage of the painting, to diagnose his nature to avoid possible incompatibilidades and to eliminate the dust and the dirt before being painted.
- 4 - Fill in defects in the substrate.
- 5 - Deal with fungicide the supports with mould.

WAY OF USE

Application notes

- Shake the product until its perfect homogened
- Dilute to the product based on the porosity and state of the support in undercoat.
- Finish with one or more coats slightly dilluted until surface is totally covered.
- Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Aerographic gun	10-20%

SYSTEM

Procedures depending of surface type

	Primer	Intermedium	Finish
Support with mould			
MAX	Fungicida	Rehabit P5	Rehabit P5+Aditivo fungicida
STD	Fungicida		Rehabit P5+Aditivo fungicida
New work			
MAX	Fijador	Rehabit P5	Rehabit P5
STD	Rehabit P5 diluido		Rehabit P5
Old paintings in bad state			
MAX	Eliminar+Fijador	Rehabit P5	Rehabit P5
STD	Eliminar+Rehabit P5 diluido		Rehabit P5
Old painting in good state			
MAX	Rehabit P5	Rehabit P5	Rehabit P5
STD	Rehabit P5 diluido		Rehabit P5

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Fecha de Alta

11-05-2021

Versión

2 - 07/01/2022 12:1

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE

Maximum recommended storage time : 24 months since its fabrication in its original packaging perfectly closed, stored indoors and at temperatures between 5° and 35°C

Information here indicated is based on our actual knowledge, laboratory testing and taking in count the practical use under specific circumstances. As it is impossible to establish an adequate description for every nature and status of the supports to be painted, we are unable to warrant the absolute reproductibility in each specific use

PACKINGS

4 L, 15 L



FAMILY
LINE

DESCRIPTION AND NATURE

Acrylic plastic paint, for decoration and protection of walls and ceilings. Ideal for generating an appearance of absolute cleanliness and freshness.

USAGES

PROPERTIES

- Whiteness
- Low odour
- High sweating
- Good covering in dry
- Good applicability

TECHNICAL CHARACTERISTICS

Referencia Color	
Finish	Matt
Specific weight	1,61± 0,05 kg/l
Viscosity	110 +/- 25 PO
Solids in volume	42± 1
Solids in weight	65± 1
VOC	Cat. a/BA 75/30 (2007/2010):0,69 g/l
Aproximated performance by coat	7-9 m ² /L
Dry to touch	(20°C HR:60%): 1 h
Dry to repaint	(20°C HR:60%): mín 3-4 h
Colours	White
	Tint with universal dye or with water, máx 5%
Classification	AFNOR: NFT. 36005 Famille I Classe 7b2

Fecha de Alta

11-05-2021

Versión

2 - 07/01/2022 12:1

SURFACE PREPAIRING

New surfaces

Cement mortars:

1. Hope until forged total (mín 30 days).
2. Clean the possible eflorescencias with abrasive spurt.
3. Neutralize the alkaline surfaces.
4. Polished surfaces: to sandpaper .
5. Clean the strange product on support.
6. Fix the weak supports with fixer.
7. Fill in defects in the substrate.

Plaster:

1. Wait till complete drying of product (20% max. Moisture level).
2. Clean the strange product on support.
3. Clean the possible eflorescencias with abrasive spurt.
4. Regulate the absorptions of the support with selladora, Locking device, or a diluted hand of he himself product
5. Polished surfaces: to sandpaper to open pore
6. Fix the weak supports with fixer.
7. Fill in defects in the substrate.

Restoring and maintenance

- 1 - Eliminate old paintings in badly been or badly adhered totally.
- 2 - Shining surfaces must be clarified, to make sure a good adhesion.
- 3 - On painted supports it must verify the solidity and anchorage of the painting, to diagnose his nature to avoid possible incompatibilidades and to eliminate the dust and the dirt before being painted.
- 4 - Fill in defects in the substrate.
- 5 - Deal with fungicide the supports with mould.

WAY OF USE

Application notes

- Shake the product until its perfect homogened
- Dilute to the product based on the porosity and state of the support in undercoat.
- Finish with one or more coats slightly dilluted until surface is totally covered.
- Do not apply product at temperatures below 5°C or any surfaces which have been exposed to sunshine.

Solvent for dilution and cleaning

Water

Way of use	Aproximate dilution
Painting brush	10-20%
Roller	10-20%
Aerographic gun	10-20%

SYSTEM

Procedures depending of surface type


	Primer	Intermedium	Finish
Support with mould			
MAX	Fungicida	Rehabit P5	Rehabit P5+Aditivo fungicida
STD	Fungicida		Rehabit P5+Aditivo fungicida
New work			
MAX	Fijador	Rehabit P5	Rehabit P5
STD	Rehabit P5 diluido		Rehabit P5
Old paintings in bad state			
MAX	Eliminar+Fijador	Rehabit P5	Rehabit P5

Fecha de Alta

11-05-2021

Versión

2 - 07/01/2022 12:1

**STD** Eliminar+Rehabit P5 diluido

Rehabit P5

Old painting in good state**MAX** Rehabit P5

Rehabit P5

Rehabit P5

STD Rehabit P5 diluido

Rehabit P5

SECURITY

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

Do not eat, neither drink, nor smoke during the application. In case of contact with eyes, wash abundantly with clean water. Keep away from children. Do not throw in darin. Keep product in dry area, under cover and temperature between 5 to 35°C. For further information, please check product safety sheet.

NOTE**PACKINGS**

4 L, 15 L