

AGUAPLAST WOOD REPAIR FILLER

Powder wood filler



GENERAL CHARACTERISTICS

USAGES

- Repairing and filling gaps on wood and timber.
- Reprofilling and shaping of wooden furniture.
- Repairing broken angles.
- Reconstitute missing wood due to decay.

CHARACTERISTICS

- Filling up to 50 mm.
- Easy to shape and smooth after setting.
- Quick drying.
- Allows sanding and overcoating after 3 hours.
- Excellent adhesion.
- Reinforced with fibers.
- Can be overcoated with most paints and varnishes for wood treatment.

SUITABILITY RATING ACCORDING TO THE SUBSTRATE

From 1 being suitable to 3 being highly suitable

SUBSTRATES	Suitability
Interior - Absorbent	
Concrete, cement and lime mortars	-
Cellular concrete, concrete blocks, sand-lime blocks	-
Ceramic bricks	-
Plasterboard, gypsum fiber board, gypsum block	-
Plaster and gypsum	-
Cement and fiber-cement boards	-
Matt Paints	-
Natural stone, stone cladding	-
Wood, timber, plywood, chipboard	3
Interior - Non absorbent	
Old coats of satin/gloss/egg shell paints	-
Old coats of oil-based, solvent-based paints	-
Sprinkle effect, decorative acrylic coatings	-
Fiberglass wall coverings, painted or not	-
Ceramic tiles, glass mosaic, glazing substrates	-
Smooth concrete	-

TECHNICAL DATA

Product	
Form	Powder
Composition	Hydraulic binders, fillers, binders, etc.
Color	Light brown
Particle size	< 200 µm
Density	Bulk in powder: 0.9 gr/cc Mixed fresh paste: 1.3 g/cm3
Application	
Temperature	5-35 °C
Tools	Spatula, Filling knife
Mixing rate	0,4 L / 1kg
Application thickness	50 mm
Working time	30'
Drying time (23°C - 65% HR)	3h
Consumption	1 kg/m2/mm
Sanding/Overcoating time	After completed drying
Interior/Exterior	Interior/Exterior

PACKING

Product Code	Packaging	Units/Carton	Palletization
70608-002	Box 1 kg	10	63 Cartons

PREPARATION AND APPLICATION

SUBSTRATE PREPARATION

Apply on dry substrates. The substrate must be cohesive, load-bearing and clean of dust, grease, wax or any other substance hindering a proper adhesion of the filler. Remove wood rot and prime if necessary. All areas contaminated with mold and/or algae must be thoroughly cleaned, then treated with FUNGISTOP or another anti-fungal agent. Protect metallic parts with BEISSIER CHAMELEON or another anti-corrosion primer. In general, substrates must be treated and prepared according to local standards. If any doubt, it is highly recommended to perform a test application on a small area to determine suitability, compatibility and application conditions.

APPLICATION

Use clean water, container and tools to mix the product. Mix in proportion 0,4 L water / 1 kg powder. Gradually pour the powder into water, stirring until an even, lump free paste is obtained. The product can be used immediately. The paste remains workable for approx. 30 minutes at 20°C. High temperatures shall shorten and cold temperatures may extend working time. Do not stir once the setting has begun. Do not add water nor powder once the setting has begun. Do not add water in excess to avoid shrinkage. Apply manually using stainless steel trowel, spatula or blade. Clean tools with water immediately after use. When working in interiors, allow air ventilation to ensure a correct drying process. Can be overcoated with any kind of varnish, wood stain, lacquer or paint.

CAUTIONS, STORAGE, HEALTH AND SAFETY

CAUTIONS

Do not apply at temperatures below 5°C or above 35 °C.
Do not apply on substrates subjected to constant humidity.

STORAGE AND SHELF LIFE.

Store away from extreme temperatures, frost, direct sunlight and humidity. Guaranteed preservation period: 3 years. The best quality is guaranteed within original unopened package. Date of manufacture can be read as printed on package and/or concluded out of batch number YDDD##. Example: Batch Nr. 314401 = 2023 May 24 (144/365). Close properly after use. Open packages should be consumed within the soonest possible.

HEALTH AND SAFETY

Consult the latest Safety Data Sheet available at www.beissier.com. Cementitious product. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear gloves and goggles. Avoid inhalation of particles when sanding. Keep out of reach of children.

DISPOSAL PROCEDURES

Dispose of waste and residues in accordance with local authority requirements. Powder to be collected, sealed tightly in bags and disposed on approved landfills. Paste must not be thrown away into drains. If recycling is not practicable, dispose of in compliance with local regulations.

Sustainable packaging

Recycled & 100% recyclable packaging. Material derived from responsible sources.



REGULATIONS AND CERTIFICATIONS

Environmental Certifications:



Note: The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.