

AGUAPLAST RAPID FILL

Quick dry exterior lightweight filler



GENERAL CHARACTERISTICS

USAGES

- Filling holes and cracks on exterior walls.
- Can be applied on concrete, cellular concrete, cement, concrete blocks, bricks, wood, etc.

SUITABILITY RATING ACCORDING TO THE SUBSTRATE

From 1 being suitable to 3 being highly suitable

SUBSTRATES	Suitability
Interior - Absorbent	
Concrete, cement and lime mortars	3
Cellular concrete, concrete blocks, sand-lime blocks	3
Ceramic bricks	3
Plasterboard, gypsum fiber board, gypsum block	3
Plaster and gypsum	3
Cement and fiber-cement boards	3
Matt Paints	3
Natural stone, stone cladding	3
Wood, timber, plywood, chipboard	3
Interior - Non absorbent	
Old coats of satin/gloss/egg shell paints	3
Old coats of oil-based, solvent-based paints	3
Sprinkle effect, decorative acrylic coatings	3
Fiberglass wall coverings, painted or not	3
Ceramic tiles, glass mosaic, glazing substrates	-
Smooth concrete	3
Exterior	
Painted facades	3
External acrylic plaster	3
Tiled facades	-
Damp substrates	-
Substrates subjected to constant humidity	-

CHARACTERISTICS

- Concrete-like rough finish.
- Can be applied in any thickness.
- No shrinking or cracking.
- Touch dry after 30'.
- Excellent adhesion.
- Fiberglass reinforced.

TECHNICAL DATA

Product	
Form	Paste
Composition	Water, light fillers, binders, etc.
Color	Grey
Particle size	1 mm
Density	1.4 g/cm ³

Application

Temperature	5-35 °C
Tools	Spatula, Filling knife
Application thickness	No limit
Working time	No limit
Drying time (23°C - 65% HR)	Touch Dry 30 minutes
Sanding/Overcoating time	After completed drying
Interior/Exterior	Interior/Exterior

PACKING

Product Code	Packaging	Units/Carton	Palletization
70056-004	Bucket 1 kg	12	54 Cartons

PREPARATION AND APPLICATION

SUBSTRATE PREPARATION

Apply on dry substrates. The substrate must be cohesive, load-bearing and clean of dust, grease, wax or any other substance hindering a proper adhesion of the filler. Remove loose or poorly bonded parts of plaster, mortars, old coats of paints, etc. Apply DELTAFIX or other consolidating primer to harden feeble and chalky substrates. If necessary, treat absorbent substrates with FIXACRYL or another stabilizing primer to reduce surface absorption. All areas contaminated with mold and/or algae must be thoroughly cleaned, then treated with FUNGISTOP or another anti-fungal agent. Protect metallic parts with BEISSIER CHAMELEON or another anti-corrosion primer. In general, substrates must be treated and prepared according to local standards. If any doubt, it is highly recommended to perform a test application on a small area to determine suitability, compatibility and application conditions.

APPLICATION

Ready to use paste. Apply manually using stainless steel trowel, spatula or blade. Clean tools with water immediately after use. When working in interiors, allow air ventilation to ensure a correct drying process. Can be overcoated with any kind of paint, finishing coating, wallpaper, etc. Decorative finishes can be applied once the surface is dry.

CAUTIONS, STORAGE, HEALTH AND SAFETY

CAUTIONS

Do not apply at temperatures below 5°C or above 35 °C.
Do not apply on substrates subjected to constant humidity.
Do not apply on glazed surfaces (tiles, mosaic, etc.).

STORAGE AND SHELF LIFE.

Store away from extreme temperatures, frost, direct sunlight and humidity. Guaranteed preservation period: 2 year. The best quality is guaranteed within original unopened package. Date of manufacture can be read as printed on package and/or concluded out of batch number YDDD##. Example: Batch Nr. 314401 = 2023 May 24 (144/365). Close properly after use.

HEALTH AND SAFETY

Consult the latest Safety Data Sheet available at www.beissier.com. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear gloves and goggles. Avoid inhalation of particles when sanding. Keep out of reach of children.

DISPOSAL PROCEDURES

Dispose of waste and residues in accordance with local authority requirements. Paste must not be thrown away into drains. If recycling is not practicable, dispose of in compliance with local regulations.

Sustainable packaging

Recycled & 100% recyclable packaging.



REGULATIONS AND CERTIFICATIONS

Applicable Norms and Certificates:

Classification EN 16566:2014 (G3S3V0W0A0C0R0)

Note: The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.